

UL-STL-C



Features:

- Low energy consumption.
- Long service life.
- IP65 waterproof.
- Not easy to generate heat.
- Safe and reliable.



Physical parameters

Model	UL-STL-C
Totallengthofstringlights	20M
Number of lamp-socket	20
Waterproof level	IP65
Lampholder Type	S14
Distance from plug to first socket	185CM
Distance from tail to last lamp socket	35CM
Lamp holder spacing	94CM
Wire diameter	20#
Lamp head to main line distance	as the picture shows
Bulb size	88*45mm
String light material	PVC
Bulb material	PET
Number of bulbs	20PCS
Power supply	220-240V-Plug-in Power

Main Electrical Components Characteristics

Input/Output Voltage	220V~240V
Frequency	50Hz/60Hz
Single String Light Power	30W
Single Bulb Power	1.5W
Color Temperature	3000K
Single bulb luminous flux	80~100LM
Color Rendering Index	80
Beam Angel	360
PF Value	>0.8
Working Temperature	-20~+40°C
Save Temperature	-20~+40°C

Precautions for use:

1. It is recommended to keep the bulb shell clean. Foreign matter on the surface of the bulb will affect the appearance and luminous effect of the product.
2. It is recommended to ensure the safety of the use of electricity in the environment.
3. The lamp bead in the bulb is a highly sensitive component, and it is necessary to avoid frequent mutation of the input voltage or excess for a long time in use.
4. In normal use, it is necessary to ensure that the lamp power supply is reliable contact.
5. Other items: It must be noted that the light output by the LED bulb is a strong light, and the naked eye should be avoided by looking directly at the LED bulb.

Special Instructions:

1. For matters not detailed, the actual object shall prevail;
2. The final interpretation of this specification belongs to the company, which is based on the actual material. Please do not inform the company if the details and parameters change.