



SPECIFICATIONS

KEY INFORMATION

Model	UL-H150W-FS
Power	150W
Luminous Efficacy	150 lm/W
CCT	5500K
Sensor	No Sensor
Beam Angle	90°
Application	Warehouse, factory, workshop, commercial and industrial lighting

ELECTRICAL

Input Voltage	220-240V AC
Frequency	50/60Hz
Power Factor	≥0.95
THD	<15%

CONSTRUCTION

Housing	Die-cast Aluminium
Lens	PC
Finish	Black
IP Rating	IP65
Mounting	Hook Mount
Packing Size	59.5 × 30 × 46 cm (6 pcs/ctn)
Carton Weight	N.W. 11.7 kg / G.W. 12.7 kg
Warranty	5 Years


DIMENSIONS (mm)

Φ277 × H146 mm

FRONT / SIDE VIEW



BOTTOM VIEW



SIDE VIEW



TOP VIEW



FEATURES

- ✓ High efficiency LED high bay for industrial applications
- ✓ Robust die-cast housing
- ✓ Long lifespan and reliable performance
- ✓ Suitable for warehouses and workshops



PHONE
+61418551100



CONTACT
Tony Psittakakis



EMAIL
tp@u-ledlighting.com.au



VIC WAREHOUSE
1/21 LINDAWAY PLACE,
TULLAMARINE
VICTORIA 3043



NSW WAREHOUSE
7 Garthowen Avenue,
Bankstown,
NSW 2200